



FNPT SIZE	A	B	C	N	L	INSTALLATION HOLE
1/2"	1.39"	2.18"	2.25"	2.18"	1.33"	1-7/16"
3/4"	1.39"	2.18"	2.25"	2.18"	1.33"	1-7/16"
1"	2.27"	3.26"	3.05"	3.06"	2.13"	2-5/16"
1-1/4"	2.27"	3.26"	3.05"	3.06"	2.13"	2-5/16"
1-1/2"	3.01"	4.58"	3.14"	4.61"	2.02"	3-1/16"
2"	3.01"	4.58"	3.14"	4.61"	2.02"	3-1/16"
3"	4.47"	6.00"	3.62"	5.99"	2.23"	4-1/2"
4"	5.64"	8.86"	6.00"	8.87"	3.73"	5-11/16"

PBG-BLK - Polypropylene - Black Glass Filled - 20% Glass Reinforced Copolymer Polypropylene

PVC - PVC Polyvinyl Chloride

PP-NAT - PP-NAT. Polypropylene - Natural

CPVC - CPVC Chlorinated Polyvinyl Chloride

PVDF-NAT - PVDF-NAT. Polyvinylidene Fluoride - Natural

**DESIGN FEATURES:**

Heavy Duty cross-sectional wall thickness to with stand high torque tightening avoiding thread stripping or damage.

Bulkheads are available on request in various other materials such as Natural Polypropylene for food applications.

PVC is manufactured with Grade Resin as a Type I Grade Industrial Fitting.

CPVC and PVDF are designed to handle higher temperature and aggressive chemical applications.